



UX10 FULLY RUGGED TABLET

- 10th Generation Intel® Core™ i7 / i5 Processor
- 10.1" FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,000 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro[™], Windows Hello face-authentication camera and multi-factor authentication options
- Detachable keyboard and multifunctional hard handle for on-the-job flexibility
- Multiple configurable options to fit diverse usage scenarios















Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform Intel® Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Platform Options: Intel® Core™ i5-10310U vPro™ Processor 1.7GHz Max. 4.4GHz with Intel® Turbo Boost Technology 6MB Intel® Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel® Core™ i7-10610U vPro™ Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

10.1" IPS TFT LCD FHD (1920 x 1200)

Protection film 1000 nits LumiBond® display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

8GB DDR4

Optional: 16GB/32GB DDR4

256GB PCIe NVMe SSD

Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen
 Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional (top side): 1D/2D imager barcode reader i, or serial port, or USB 3.2 Gen 1 Type-A, or USB 3.2 Gen 1 Type-C port, or LAN port (RJ-45), or VGA port ii, or HF RFID reader

Optional (right side): fingerprint reader, or serial port+LAN port (RJ-45), or HF RFID reader $^{\rm iv}$

Optional (back side): smart card reader, or bridge battery, or bridge battery+smart card reader ^v

I/O Interface

FHD webcam x 1 xi 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 HDMI x 1

Docking Connector x 1 Optional: Windows Hello face-authentication camera (front-facing) x 1 ^{xi} Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax Bluetooth (v5.2) vi Optional: Dedicated GPS iii Optional: 4G LTE mobile broadband with integrated GPS iii

Optional: 10/100/1000 base-T Ethernet

Security Feature

TPM 2.0 Kensington Lock Optional: Intel® vPro™ Technology Optional: HF RFID reader ^{i,ii}

Optional: Fingerprint reader ™ Optional: Smart card reader in

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 4200mAh; min.4080mAh) x 1

Optional: High capacity battery (10.8V, 9240mAh) x 1 Optional: Bridge battery

Dimension (W x D x H) & Weight

276.8 x 194.5 x 23.5 mm (10.89" x 7.65" x 0.92"), 1.22 kg (2.68 lbs) vii

Rugged Feature MIL-STD-810H certified IP65 certified WIL-STD-461G certified wii Vibration & 6 feet (1.8m) drop resistant ix.x e-Mark certified for vehicle usage Optional: ANSI / UL 121201, CSA C22.2 NO. 213 Optional: Salt fog certified

Environmental Specification

Temperature

- Operating: -29°C to 63°C / -20°F to 145°F -51°C to 71°C / -60°F to 160°F Humidity
- 95% RH , non-condensing

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager XIII
Optional: Absolute Persistence®

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC Adapter (65W, 100-240VAC) Capacitive Stylus

Optional:

Carry Bag

Carry Bag Folio Case Battery (11.1V, typical 4200mAh; min. 4080mAh) High capacity Battery (10.8V, 9240 mAh) Multi-bay Charger (Dual Bay) Multi-Bay Charger (Eight-Bay) AC Adapter (65W, 100-240VAC) Office Dock AC Adapter(90W, 100-240VAC) MIL-STD-461 Certified AC Adapter (90W, 115-230VAC)

115-230VAC) Vehicle Adapter (120W, 11-32VDC)

Digitizer Pen Capacitive Stylus Protection Film

Hand Strap
Shoulder Strap (2-point)
Shoulder Harness (4-point; handsfree)
Detachable Keyboard
Vehicle Dock

100W Type-C Adaptor xiii

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

3 years Bumper-to-Bumper

- 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (RJ45), USB 3.2 Gen 1 Type-A, USB 3.2 Gen 1 Type-C port and VGA port are mutually exclusive options.
- Supports GPS and Glonass. Fingerprint scanner, HF RFID reader, and serial port + LAN port (RJ45) are mutually exclusive options.
- Smart card reader, bridge battery and bridge battery + smart card reader are mutually
- exclusive options.
 Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- vii Weight and dimensions vary from configurations and optional accessories viii MIL-STD-461G 90W AC adapter sold separately. ix Drop test results vary from configurations and optional accessories.
- Tested by an independent third-party test lab following MIL-STD-810H.
- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- Available when barcode reader option is selected. xiii Do not support the configurations with Discrete Graphic Card.

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	1
VGA		1
Microphone		1
Audio Output		1
DC in Jack	1	1
USB	USB 3.2 Gen1 x 2 USB 2.0 x 2	USB 3.2 Gen1 x 2 USB 2.0 x 2
LAN	1	1
HDMI		1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	
Kensington Lock	1	1



GETACULAL LINIOLOGY CORPORATION

5.፲፱፻₽፱ ibdingsAֈՠֈ֍՜ւշ/በአ/ድ፭-ểctilæn3ቼ,αNangang Rd., Maainingada, gMbhìsho ishi inipeFFB iByBJ 1.5568e dakinnagodoho O.C. Tel: 948986(82)-2229(912) 728878222



Copyright © 2029 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V01M0BY29U8W