


### Overview

### HP ProDesk 600 G1 Desktop Mini Business PC




1. 3.5mm headphone output and microphone jacks
2. (2) Front USB 3.0 ports; one featuring Fast Charge capability
3. Power button and PC status LED

#### Not Shown

- |          |  |
|----------|--|
| Slots    | (1) internal M.2 connector for optional wireless NIC<br>(1) internal M.2 connector for optional SSD drive  |
| Bays     | (1) 2.5" internal storage drive bay  |
| Rear I/O | (2) USB 3.0 ports; (2) USB 2.0 ports<br>(1) VGA video port; (2) DisplayPort with multi-stream video ports<br>(1) RJ-45 network connector<br>3.5mm audio out jack |
| VESA     | Support for VESA 100 mounting system on bottom of PC chassis   |

### Overview

### HP ProDesk 600 G1 Small Form Factor Business PC




- 1 Power button and PC status LED
- 2 3.5" external drive bay; used for installing a Media Card Reader or 2<sup>nd</sup> data storage drive
- 3 Slim drive bay supporting an optical disk drive (located behind removable bezel)
- 4 (2) USB 3.0 ports, (2) USB 2.0 ports
- 5 3.5mm headphone output and microphone jack

#### Not Shown

- |          |   |
|----------|---|
| Slots    | (1) PCI Express x16 graphics connector<br>(3) PCI Express x1 accessory connectors   |
| Bays     | (1) 2.5" internal storage drive bay<br>(1) 3.5" internal storage drive bay  |
| Rear I/O | (2) USB 3.0 ports; (4) USB 2.0 ports<br>(1) VGA video port; (2) DisplayPort with multi-stream video ports<br>(1) RJ-45 network connector<br>(1) RS-232 serial port<br>3.5mm audio in/out jacks<br>PS/2 keyboard and mouse ports |

### Overview

### HP ProDesk 600 G1 Tower Business PC



- 1 Power button and PC status LED
- 2 Slim drive bay supporting an optical disk drive (located behind removable bezel)
- 3 5.25" half height external drive bay (located behind removable bezel)
- 4 3.5" external drive bay; used for installing a Media Card Reader
- 5 (2) USB 3.0 ports, (2) USB 2.0 ports
- 6 3.5mm headphone output and microphone jack

#### Not Shown

- Slots
  - (1) PCI Express x16 graphics connector
  - (3) PCI Express x1 accessory connector
- Bays
  - (1) 2.5" internal storage drive bay
  - (2) 3.5" internal storage drive bay
- Rear I/O
  - (2) USB 3.0 ports; (4) USB 2.0 ports
  - (1) VGA video port; (2) DisplayPort with multi-stream video ports
  - (1) RJ-45 network connector
  - (1) RS-232 serial port
  - 3.5mm audio in/out jacks
  - PS/2 keyboard and mouse ports

### Overview

#### At A Glance

- Choice of Desktop Mini, Small Form Factor or Tower chassis options
- PC chassis and all internal components and modules are manufactured with low halogen content
- HP developed and engineered UEFI BIOS supporting security, manageability and software image stability
- Intel® Q85 chipset supporting Intel 4th generation Core processors, featuring integrated Intel HD Graphics and Intel® Standard Manageability Technology
- Processor support up to 84W (TWR/SFF), 35W (DM)
- Intel® Ethernet Connection I217L GbE LOM integrated network connection
- DDR3 Synchronous Dynamic Random Access Memory (SDRAM)
- Multi-independent monitor support via VGA and dual digital DisplayPort video interfaces with multi-stream
- Discrete graphics options available for SFF and TWR platforms
- DTS+ Sound audio management software
- Standard and high efficiency energy saving power supply options
- ENERGY STAR® qualified and certified EPEAT® Gold models
- Guaranteed lengthy purchase lifecycles and image stability

### Technical Specifications - Graphics

#### CHIPSET

Intel® Q85 Express	<b><u>DM</u></b> <b>X</b>	<b><u>SFF/TWR</u></b> <b>X</b>
--------------------	------------------------------	-----------------------------------

#### PROCESSOR

<b>Intel® 4th Generation Core™ i7 Processors</b>	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
<u>Intel® Core™ i7-4765T Processor</u> Up to 3.0 GHz Max. Turbo Frequency (2.0 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate Supports Intel® Stable Image Platform Program (SIPP)	<b>X</b>	

<u>Intel® Core™ i7-4770 Processor</u> Up to 3.9 GHz Max. Turbo Frequency (3.4 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate Supports Intel® Stable Image Platform Program (SIPP)		<b>X</b>
--	--	----------

<b>Intel® 4th Generation Core™ i5 Processors</b>	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
<u>Intel® Core™ i5-4570 Processor</u> Up to 3.6 GHz Max. Turbo Frequency (3.2 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate Supports Intel® Stable Image Platform Program (SIPP)		<b>X</b>

<u>Intel® Core™ i5-4570T Processor</u> Up to 3.6 GHz Max. Turbo Frequency (2.9 GHz base frequency) 4 MB cache, 4 cores, 4 threads Intel HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate Supports Intel® Stable Image Platform Program (SIPP)	<b>X</b>	
---	----------	--

<u>Intel® Core™ i5-4670 Processor</u> Up to 3.8 GHz Max. Turbo Frequency (3.4 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate Supports Intel® Stable Image Platform Program (SIPP)		<b>X</b>
--	--	----------

<b>Intel® 4th Generation Core™ i3 Processors</b>	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
<u>Intel® Core™ i3-4130 Processor</u> 3.4 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate		<b>X</b>

### Technical Specifications - Graphics

<p><u>Intel® Core™ i3-4130T Processor</u>            2.9 GHz base frequency            3 MB cache, 2 cores, 4 threads            Intel HD Graphics 4400            Supports DDR3 memory up to 1600 MT/s data rate</p>	<b>X</b>	
<p><u>Intel® Core™ i3-4330 Processor</u>            3.5 GHz base frequency            4 MB cache, 2 cores, 4 threads            Intel HD Graphics 4600            Supports DDR3 memory up to 1600 MT/s data rate</p>		<b>X</b>
<p><u>Intel® Core™ i3-4330T Processor</u>            3.0 GHz base frequency            4 MB cache, 2 cores, 4 threads            Intel HD Graphics 4600            Supports DDR3 memory up to 1600 MT/s data rate</p>	<b>X</b>	
<p><u>Intel® Core™ i3-4340 Processor</u>            3.6 GHz base frequency            4 MB cache, 2 cores, 4 threads            Intel HD Graphics 4600            Supports DDR3 memory up to 1600 MT/s data rate</p>		<b>X</b>
<p><b>Intel® 4th Generation Pentium™ Processors</b></p>	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
<p><u>Intel® Pentium G3220 Processor</u>            3.0 GHz base frequency            3 MB cache, 2 cores, 2 threads            Intel HD Graphics            Supports DDR3 memory up to 1333 MT/s data rate</p>		<b>X</b>
<p><u>Intel® Pentium™ G3220T Processor</u>            2.6 GHz base frequency            3 MB cache, 2 cores, 2 threads            Intel HD Graphics            Supports DDR3 memory up to 1333 MT/s data rate</p>	<b>X</b>	
<p><u>Intel® Pentium G3420 Processor</u>            3.2 GHz base frequency            3 MB cache, 2 cores, 2 threads            Intel HD Graphics            Supports DDR3 memory up to 1600 MT/s data rate</p>		<b>X</b>
<p><u>Intel® Pentium™ G3420T Processor</u>            2.7 GHz base frequency            3 MB cache, 2 cores, 2 threads            Intel HD Graphics            Supports DDR3 memory up to 1600 MT/s data rate</p>	<b>X</b>	
<p><u>Intel® Pentium G3430 Processor</u></p>		<b>X</b>

### Technical Specifications - Graphics

3.3 GHz base frequency  
 3 MB cache, 2 cores, 2 threads  
 Intel HD Graphics  
 Supports DDR3 memory up to 1600 MT/s data rate

#### Intel® 4th Generation Celeron™ Processors

**DM**

**SFF/TWR**

#### Intel® Celeron™ G1820 Processor\*

2.7 GHz base frequency  
 2 MB cache, 2 cores, 2 threads  
 Intel HD Graphics  
 Supports DDR3 memory up to 1333 MT/s data rate  
 \*Available in February

**X**

#### Intel® Celeron™ G1820T Processor

2.4 GHz base frequency  
 2 MB cache, 2 cores, 2 threads  
 Intel HD Graphics  
 Supports DDR3 memory up to 1333 MT/s data rate

**X**

#### Intel® Celeron™ G1830 Processor\*

2.8 GHz base frequency  
 2 MB cache, 2 cores, 2 threads  
 Intel HD Graphics  
 Supports DDR3 memory up to 1333 MT/s data rate  
 \*Available in February

**X**

### GRAPHICS\*

\*NOTE: AMD and NVIDIA graphics cards are not available on configurations with the preinstalled Windows 10 operating system. Configurations with the Windows 10 downgrade to Windows 7 operating system will allow for upgrading to Windows 10 with AMD and NVIDIA graphics cards through graphics driver installation from [hp.com](http://hp.com).

**Intel HD Graphics on all models (integrated on processor)**

**DM**

**SFF/TWR**

**X**

**X**

#### **Optional Discrete Graphics Solutions**

**DM**

**SFF/TWR**

AMD Radeon HD 8350 (1GB) PCIe x16  
 AMD Radeon HD 8490 (1GB) PCIe x 16  
 NVIDIA NVS 310 (512 MB) PCIe x16  
 NVIDIA NVS 315 (1GB) PCIe x 16  
 NVIDIA GeForce GT630 (2 GB) FH PCIe x16

**X**

**X**

**X**

**X**

**TWR only**

#### **Adapters and Cables**

**DM**

**SFF/TWR**

HP DMS-59 to Dual DisplayPort Cable  
 HP DMS-59 to Dual DVI Cable  
 HP DMS-59 to Dual VGA Cable  
 HP DisplayPort to DisplayPort Cable  
 HP DisplayPort to DVI-D Adapter

**X**

**X**

**X**

**X**

**X**

**X**

**X**

### Technical Specifications - Graphics

HP DisplayPort to HDMI Adapter	X	X
HP DisplayPort to VGA Adapter	X	X
HP Serial Port Adapter		X
HP Parallel Port Adapter		X

### STORAGE\*

	<u>DM</u>	<u>SFF/TWR</u>
<b>Hard Disk Drive (HDD)</b>		
320 GB 7200 rpm HDD		X
500 GB 7200 rpm HDD	X	X
500 GB 7200 rpm SED HDD	X	X
500 GB 10K rpm HDD		X
1 TB 7200 rpm HDD		X
1 TB 10K rpm HDD		X
2 TB 7200 rpm HDD		X
<b>Solid State Hybrid Drives (SSHD)</b>	<u>DM</u>	<u>SFF/TWR</u>
500 GB SSHD (8 GB cache)	X	X
1 TB SSHD (8 GB cache)	X	X
<b>Solid State Drives (SSD) &amp; Self-encrypting Solid State Drives (SED)</b>	<u>DM</u>	<u>SFF/TWR</u>
120 GB Opal SED	X	X
128 GB SSD		X
128 GB M.2 PCIe SSD	X	
128 GB Opal SED	X	X
180 GB Opal SED	X	X
256 GB SED		X
256 GB Opal SED	X	X
<b>Optical Disc Drives</b>	<u>DM</u>	<u>SFF/TWR</u>
Slim DVD-ROM		X
Slim BDXL Blu-ray Writer		X
Slim SuperMulti DVD Writer		X
HH SuperMulti ODD		TWR only
<b>Removable</b>	<u>DM</u>	<u>SFF/TWR</u>
HP Slim Removable SATA HDD Frame/Carrier		X

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

### MEMORY

Form Factor	Type	Maximum	# of Slots
-------------	------	---------	------------



### Technical Specifications - Graphics

Desktop Mini	DDR3 non-ECC up to 1600 MT/s	16 GB	2 SODIMM
Small Form Factor	DDR3 non-ECC Up to 1600 MT/s	32 GB	4 DIMM
Tower	DDR3 non-ECC Up to 1600 MT/s	32 GB	4 DIMM

**NOTE:** For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

Memory modules support data transfer rates up to 1600 MT/s; actual data rate is determined by the system's configured processor. See processor specifications for supported memory data rate.

### NETWORKING/COMMUNICATIONS

	<u>DM</u>	<u>SFF/TWR</u>
<b>Ethernet (RJ-45)</b>		
Intel I217LM Gigabit Network Connection (standard)	X	X
Intel Ethernet I210-T1 PCIe x1 Gb Network Interface Card (optional)		X
<b>Wireless</b>	<u>DM</u>	<u>SFF/TWR</u>
Intel Centrino Advanced-N 6205 802.11 a/b/g/n PCI Express x1 Wireless Network Connection (optional)		X
Intel 7260 802.11 a/b/g/n PCIe x1 (optional) (Available in December)		X
Intel Wireless-N 7260 802.11 M.2 a/b/g/n NIC Card (optional)	X	

### AUDIO/MULTIMEDIA

	<u>DM</u>	<u>SFF/TWR</u>
<b>Audio</b>		
HD audio with Realtek ALC221 codec (all ports are stereo)	X	X
DTS Sound + audio management technology	X	X
Microphone* and headphone front ports (3.5mm)	X	X
Line-out and Line-In rear Ports* (3.5mm)	<b>Line out only</b>	X
Multi-streaming capable*	X	X
Internal speaker (standard)	X	X

\* The front microphone port is re-taskable as a Line-in, Microphone-in or Headphone-out port. Rear audio input ports are re-taskable as a Line-in or Microphone-in port. External speakers must be powered externally. Multi-streaming can be enabled in the Realtek control panel to allow independent audio streams to be sent to/from the front and rear jacks. This allows for different audio applications to use separate audio ports on the system. For example, the front jacks could be used with a headset for a communications application while the rear jacks are being used with external speakers and a multimedia application.

### KEYBOARDS AND POINTING DEVICES

	<u>DM</u>	<u>SFF/TWR</u>
<b>Keyboard</b>		

### Technical Specifications - Graphics

HP PS/2 Keyboard		<b>X</b>
HP USB Keyboard	<b>X</b>	<b>X</b>
USB Smart Card (CCID) Keyboard	<b>X</b>	<b>X</b>
HP USB and PS/2 Washable Keyboard	<b>X</b>	<b>X</b>
HP Wireless Keyboard and Mouse Combo*	<b>X</b>	<b>X</b>

\*Keyboard contains 25% post-consumer recycled plastic material.

<b>Mice</b>	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
HP PS/2 Mouse		<b>X</b>
HP USB Mouse	<b>X</b>	<b>X</b>
HP USB 1000dpi Laser Mouse	<b>X</b>	<b>X</b>
HP USB and PS/2 Washable Mouse	<b>X</b>	<b>X</b>

### HP BIOS

Key features of the HP BIOS include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP ProDesk 600 G1 Series Business PC into the enterprise, such as PXE, remote configuration, remote control, and F10 Setup support for 12 languages.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- UEFI specification 2.1
- Computrace agent – For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Business Desktop computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Business Desktop computers, including BIOS updates from within DOS (DOSFlash), BIOS updates from within Windows (HPQFlash), HP Client Manager, and fail-safe recovery. In addition, the HP Business Desktop BIOS Utilities tool enables replicated BIOS setup throughout the Enterprise; it is available from within the BIOS software and from the support website.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery.

#### Additional HP BIOS Features

- Power-On password – Helps prevent an unauthorized user from powering on the system.
- Administrator password – Also known as the setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS version cannot be changed and changes cannot be made to BIOS settings using F10 setup or under the OS.
- Advanced Configuration and Power Interface (ACPI) – Represents a significant innovation in power and configuration management, allowing operating systems and applications to manage power based on activity and usage. HP Elite models use ACPI to provide power conservation features.

S5 Max Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 1W in S5 (when turned off). When S5 Max Power Savings feature is enabled power to slots is turned off along with WOL functionality.

### SECURITY

### Technical Specifications - Graphics

	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
Trusted Platform Module (TPM) 1.2	X	X
SATA port disablement (via BIOS)	X	X
Drive lock	X	X
Intel® Identify Protection Technology (IPT) <sup>1</sup>	X	X
Serial, parallel, USB enable/disable (via BIOS)		X
Optional USB Port Disable at factory (user configurable via BIOS)	X	X
Removable media write/boot control	X	X
Power-On password (via BIOS)	X	X
Setup password (via BIOS)	X	X
HP Chassis (1 bay) Security Kit		<b>TWR only</b>
Solenoid Hood Lock / Sensor		X
Support for chassis padlocks and cable lock devices	X	X

<sup>1</sup>Models configured with Intel Core processors have the ability to utilize advanced security protection for online transactions. IPT, used in conjunction with participating web sites, provides double identity authentication by adding a hardware component in addition to the usual user name and password. IPT is initialized through an HP Client Security module

### ENVIRONMENTAL & REGULATORY

ENERGY STAR® qualified models available

EPEAT® registered where applicable/supported. See [epeat.net](http://epeat.net) for registration status by country.

Low halogen (chassis, all internal components and modules)

TAA compliant

### Ports

#### I/O Ports - Standard

	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
USB 2.0	2 (rear)	2 (front); 4 (rear)
USB 3.0	2 (front) with one featuring Fast Charge capability; 2 (rear)	2 (front); 2 (rear)
Serial (RS-232)	N/A	1
PS/2	N/A	1 keyboard (purple) 1 mouse (green)
Audio	3.5mm headphone & combo jack (front) 3.5mm audio out jack (rear)	3.5mm headphone & combo jack (front) 3.5mm audio in & out jacks (rear)
Network Interface	1 RJ-45	1 RJ-45

#### I/O Ports - Optional

	<b><u>DM</u></b>	<b><u>SFF/TWR</u></b>
2nd Serial (RS-232)	N/A	1
Parallel	N/A	1

### SLOTS

### Technical Specifications - Graphics

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	
PCI Express x1 (v2.0)		N/A	3 ea. ea. 2.5" low profile 4.2" full height 6.6" length 6.6" length 10W max. power 10W max. power	3
PCI Express x16 (v3.0)		N/A	1 ea. ea. 2.5" low profile 4.2" full height 6.6" length 6.6" length 35W max. power 75W max. power	1

M.2

### BAYS

	<u>DM</u>	<u>SFF/TWR</u>
Media Card Reader	N/A	1
Slim Optical Disc Drive	N/A	1
3.5" internal storage drive	N/A	1 – SFF 1 – TWR
2.5" internal storage drive	1	1

### SERVICE AND SUPPORT

On-site Warranty 1: Three-year (3-3-3) limited warranty delivers three years of on-site, next business day 2 service for parts and labor and includes free telephone support 3 24 x 7. Three-year onsite and labor are not available in all countries. Service offers terms up to 5 years by choosing a Care Pack. To choose the right level of service for your HP product, visit HP Care Pack Central: [hp.com/go/cpc](http://hp.com/go/cpc)

NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region.

NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

NOTE 3: Technical telephone support applies only to HP-configured and third-party HP qualified hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

### OPERATING SYSTEMS

#### Preinstalled

Windows 10 Pro 64\*

Windows 10 Home 64\*

Windows 8.1 Pro 64\*

Windows 8.1 64\*

Windows 7 Professional 64 (available through downgrade rights from Windows 10 Pro)\*\*

Windows 7 Professional 32 (available through downgrade rights from Windows 10 Pro)\*\*

Windows 7 Professional 64 (available through downgrade rights from Windows 8.1 Pro)\*\*\*

Windows 7 Professional 32 (available through downgrade rights from Windows 8.1 Pro)\*\*\*

### Technical Specifications - Graphics

Windows 7 Professional 64\*  
Windows 7 Professional 32\*

#### Pre-installed (Other)

FreeDOS 2.0  
Novell SUSE Linux Enterprise Desktop 11

#### Web-supported

Windows 10 Pro 64  
Windows 10 Home 64  
Windows 8.1 Pro 64  
Windows 8.1 64  
Windows 7 Professional 64 (available through downgrade rights from Windows 10 Pro)  
Windows 7 Professional 32 (available through downgrade rights from Windows 10 Pro)  
Windows 7 Professional 64 (available through downgrade rights from Windows 8.1 Pro)  
Windows 7 Professional 32 (available through downgrade rights from Windows 8.1 Pro)  
Windows 7 Professional 64  
Windows 7 Professional 32  
Windows 10 Enterprise 64  
Windows 8.1 Enterprise 64  
Windows 7 Enterprise 64  
Windows 7 Enterprise 32

\*Note: Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.microsoft.com>.

\*\*This system is preinstalled with Windows 7 Pro software and also comes with a license and media for Windows 10 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

\*\*\*This system is preinstalled with Windows 7 Pro software and also comes with a license and media for Windows 8.1 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS			
Included	Windows 7	Windows 8.1	Windows 10

### Technical Specifications - Graphics

<b>BIOS</b>	<p>HP BIOSphere<sup>1</sup>                      HP DriveLock                      HP BIOS Protection<sup>3</sup></p> <p>BIOS Update via Network                      Master Boot Record Security                      Power On Authentication                      Pre-Boot Security                      Secure Erase<sup>6</sup></p> <p>Absolute Persistence Module<sup>7</sup></p>	<p>HP BIOSphere<sup>1</sup>                      HP DriveLock                      HP BIOS Protection<sup>3</sup>                      HP Disk Sanitizer<sup>4</sup></p> <p>BIOS Update via Network                      Master Boot Record Security                      Power On Authentication                      Pre-Boot Security                      Secure Erase<sup>6</sup>                      Hybrid Boot                      Measured Boot                      Secure Boot                      Absolute Persistence Module<sup>7</sup></p>	<p>HP BIOSphere<sup>1</sup>                      HP DriveLock                      HP BIOS Protection<sup>3</sup></p> <p>BIOS Update via Network                      Master Boot Record Security                      Power On Authentication                      Pre-Boot Security                      Secure Erase<sup>6</sup>                      Hybrid Boot                      Measured Boot                      Secure Boot                      Absolute Persistence Module<sup>7</sup></p>
<b>Multimedia</b>	<p>CyberLink Power DVD, BD                      CyberLink Power2Go (Secure Burn)                      CyberLink YouCam BE</p>	<p>CyberLink Power DVD, BD                      CyberLink Power2Go (Secure Burn)</p>	<p>CyberLink Power DVD, BD                      CyberLink Power2Go (Secure Burn)</p>

	Windows 7	Windows 8.1	Windows 10
<b>Communication</b>	<p>Intel® Wireless Display (WiDi)                      Software for Windows <sup>5</sup>                      Native Miracast Support<sup>8</sup></p>	<p>Intel® Wireless Display (WiDi)                      Software for Windows <sup>5</sup>                      Native Miracast Support<sup>8</sup></p>	<p>Intel® Wireless Display (WiDi)                      Software for Windows <sup>5</sup>                      Native Miracast Support<sup>8</sup></p>
<b>HP Value Add</b>	<p>HP ePrint Driver<sup>9</sup>                      HP Recovery Manager                      HP Support Assistant                      HP Recovery Disk Creator</p>	<p>HP ePrint Driver<sup>9</sup>                      HP Recovery Manager                      HP Support Assistant                      HP Recovery Disk Creator</p>	<p>HP ePrint Driver<sup>9</sup>                      HP Recovery Manager                      HP Support Assistant                      Windows 10 Welcome App                      HP Recovery Disk Creator</p>
<b>3<sup>rd</sup> Party</b>	<p>Foxit PhantomPDF Express for HP</p>	<p>Foxit PhantomPDF Express for HP</p>	<p>Foxit PhantomPDF Express for HP</p>
<b>Microsoft Products</b>	<p>Buy Office                      Bing Search                      Skype</p>	<p>Buy Office                      Bing Search                      Skype</p>	<p>Buy Office                      Bing Search                      Skype</p>
<b>Manageability</b>	<p>HP Drive Packs<sup>10</sup>                      HP SoftPaq Download Manager (SDM)                      HP System Software Manager (SSM)<sup>10</sup>                      HP Client Catalog <sup>10</sup>                      HP CIK for Microsoft SCCM <sup>10</sup>                      LANDESK Management <sup>11</sup>                      HP BIOS Config Utility (BCU) <sup>10</sup></p>	<p>HP Drive Packs<sup>10</sup>                      HP SoftPaq Download Manager (SDM)                      HP System Software Manager (SSM) <sup>10</sup>                      HP Client Catalog <sup>10</sup>                      HP CIK for Microsoft SCCM <sup>10</sup>                      LANDESK Management <sup>11</sup>                      HP BIOS Config Utility (BCU) <sup>10</sup></p>	<p>HP Drive Packs<sup>10</sup>                      HP SoftPaq Download Manager (SDM)                      HP System Software Manager (SSM) <sup>10</sup>                      HP Client Catalog <sup>10</sup>                      HP CIK for Microsoft SCCM <sup>10</sup>                      LANDESK Management <sup>11</sup>                      HP BIOS Config Utility (BCU) <sup>10</sup>                      Discover HP Touchpoint Manager</p>

For more information on HP Client Management Solutions refer to: <http://www.hp.com/go/clientmanagement>.

### Technical Specifications - Graphics

	Windows 7	Windows 8.1	Windows 10
<b>Security</b>	Absolute Persistence Module <sup>7</sup> HP Device Access Manager HP Drive Encryption <sup>12</sup> HP Disk Sanitizer External Edition HP Security Manager Microsoft Security Essentials <sup>14</sup>	Absolute Persistence Module <sup>7</sup> HP Device Access Manager HP Drive Encryption <sup>12</sup>  HP Disk Sanitizer External Edition HP Security Manager Microsoft Defender	Absolute Persistence Module <sup>7</sup>  HP Drive Encryption <sup>12</sup>  HP Disk Sanitizer External Edition HP Security Manager Microsoft Defender
<b>Standard</b>	Smart Card Reader Security lock slot Preboot Authentication	Smart Card Reader Security lock slot Preboot Authentication	Smart Card Reader Security lock slot Preboot Authentication

**NOTE:** The Absolute Persistence agent is shipped turned off, and must be activated by customers when they purchase a subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S.

For more information on HP Client Security Software Suite, refer to <http://www.hp.com/go/clientsecurity>.

**Footnotes:**

1 Available only on business PCs with HP BIOS.

3 May require a manual recovery step if all copies of BIOS are compromised or deleted

4 For the use cases outlined in the DOD 5220.22-M Supplement. Only supports traditional Hard Drives.

5 Integrated Intel® Wi-Di Display is available on select configurations only and requires a separate projector, TV or monitor with an integrated or external Wi-Di receiver. For more information on Intel® Wi-Di Display visit [www.intel.com/go/wirelessdisplay](http://www.intel.com/go/wirelessdisplay)

6 For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88.

7 Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit:

<http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

8 Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming media players that also support Miracast. You can use Miracast to share what you're doing on your PC and present a slide show. For more information: <http://windows.microsoft.com/en-us/windows-8/project-wireless-screen-miracast>

9 Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see [www.hp.com/go/eprintcenter](http://www.hp.com/go/eprintcenter)). Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.

10 Not preinstalled, however available on manageability website.

11 Subscription required.

12 Requires Windows. Data is protected prior to Drive Encryption login. Turning the PC off or into hibernate logs out of Drive Encryption and prevents data access.

14 Opt in and internet connection required for updates.

### Intel HD Graphics

**VGA Controller**

Integrated

### Technical Specifications - Graphics

<b>DisplayPort</b>	Multimode capable; supports HDCP, Display Port Audio (2 streams), HBR2 link rates and Multi-Stream Technology for a maximum of 3 displays (including the integrated panel)	
<b>Bus Type</b>	N/A	
<b>RAMDAC</b>	N/A	
<b>Memory</b>	<p>Intel graphics do not have dedicated memory but utilizes some of the computer's system memory. The amount of memory used for graphics depends on the amount of system memory installed, BIOS settings, operating system, and system load. 32 MB is pre-allocated for graphics use at system boot time. Additional memory can be allocated at boot time by the BIOS for PAVP (Protected Audio Video Playback) support for playback of protected video content.</p> <p>Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.</p>	
<b>Maximum Graphics Memory</b>	Microsoft Windows 7	Windows 8.1
	Up to 1.7GB	Up to 1.8GB
	Note: the actual amount of maximum graphics memory can be less than the amounts listed above depending upon your computer's configuration.	
<b>Maximum Color Depth</b>	32 bits/pixel	
<b>Graphics/Video API Support</b>	<p>4th Generation Core processors:</p> <ul style="list-style-type: none"> <li>• The Processor Graphics contains a refresh of the seventh generation graphics core enabling substantial gains in performance and lower power consumption. Up to 16 EU support.</li> <li>• Next Generation Intel Clear Video Technology HD Support is a collection of video playback and enhancement features that improve the end user's viewing experience             <ul style="list-style-type: none"> <li>○ Encode/transcode HD content</li> <li>○ Playback of high definition content including Blu-ray Disc</li> <li>○ Superior image quality with sharper, more colorful images</li> </ul> </li> <li>• DirectX Video Acceleration (DXVA) support for accelerating video processing             <ul style="list-style-type: none"> <li>○ Full AVC/VC1/MPEG2 HW Decode</li> </ul> </li> <li>• Advanced Scheduler 2.0, 1.0</li> <li>• Windows 7, Windows 8, Linux OS Support</li> <li>• DirectX 11.1</li> <li>• OpenGL 4.0</li> <li>• Open CL 1.2</li> </ul>	

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rates
800x600	60 Hz
1024x768	60 Hz
1152x864	60 Hz
1280x600	60 Hz
1280x720	60 Hz
1280x800	60 Hz



### Technical Specifications - Graphics

1280x960	60 Hz
1280x1024	60 Hz
1360x768	60 Hz
1366x768	60 Hz
1400x1050	60 Hz
1440x900	60 Hz
1600x900	60 Hz
1600x1200*	60 Hz
1680x1050	60 Hz
1920x1080	60 Hz
1920x1200*	60 Hz
1920x1440*	60 Hz
2560x1440*	60 Hz
2560x1600*	60 Hz
3840x2160*	60 Hz

\* Only supported on displays connected to the external DisplayPort connector.

### AMD Radeon HD 7650A Graphics Card

<b>Form Factor</b>	MXM 3.0
<b>Graphics Controller</b>	AMD Radeon HD 7650A
<b>Core Clock</b>	600MHz
<b>Memory Clock</b>	800MHz
<b>Memory</b>	2GB, DDR3, 128-bit wide
<b>Bus Type</b>	MXM
<b>Max. Power</b>	35W
<b>Power Source Support</b>	12V and 19V
<b>3D API Support</b>	DX11, SMS
<b>HDCP Support</b>	Yes
<b>Display Max. Resolution</b>	Digital 2560 x 1600 Analog 2048 x 1536
<b>Supported Graphics APIs</b>	DX11, OpenGL, full 1080p BD (H264) playback in hardware, Multi-Stream DisplayPort support

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rates
800 x 600	60 Hz

### Technical Specifications - Graphics

1024 x 768	60 Hz
1280 x 720	60 Hz
1280 x 768	60 Hz
1280 x 1024	60 Hz
1360 x 768	60 Hz
1440 x 900	60 Hz
1600 x 900	60 Hz
1680 x 1050	60 Hz
1920 x 1080	60 Hz

### NVIDIA NVS 310 Graphics Card

<b>Introduction</b>	<p>The NVIDIA® NVS™ 310 Graphics Card is a PCI Express low profile form factor graphics add-in card targeted as an active low cost graphics solution for the corporate business and enterprise markets.</p> <p>The NVIDIA® NVS 310 graphics card is an ideal solution for customers requiring a small form factor graphics add-in card for either standard or small form factor PC designs.</p>	
<b>Performance and Features</b>	<p>The NVIDIA® NVS 310 Graphics Card offers 512 MB of ultrafast DDR3 memory and is capable of supporting up to 2 displays.</p> <p>DisplayPort connector supports multimode technology to support connection to DVI-D, VGA and HDMI monitors with optional adapters in kits NR078AA, FH973AT, BP937AA, AS615AA.</p> <p>For a DisplayPort to DisplayPort connections use the optional DisplayPort Cable Kit VN567AA.</p>	
<b>Form Factor</b>	Low Profile: 2.713 × 6.15 in	
<b>Graphics Controller</b>	NVIDIA® NVS 310	
<b>Memory Clock</b>	875MHz	
<b>Memory Size</b>	512 MB DDR3	
<b>Memory Bandwidth</b>	14 GB/s	
<b>Max. Power</b>	19.5W	
<b>Display Max. Resolution</b>	Up to 2560 x 1600 (digital display) per display	
<b>Display Output</b>	Up to 2 displays in the following configurations	
	DisplayPort output:	<ul style="list-style-type: none"> <li>• Drives two DisplayPort enabled digital display at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking, when connected natively using the 2 DisplayPort connectors on the NVS 310 graphics card</li> <li>• Supports 2 monitors up to resolution of 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort Multi-Stream topology technology.</li> </ul>

### Technical Specifications - Graphics

	DVI-D output:	<ul style="list-style-type: none"> <li>• Drives two digital display at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors</li> <li>• Drives two digital display at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors</li> </ul>
	HDMI output:	<ul style="list-style-type: none"> <li>• NVS 310 is capable of driving two high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors</li> </ul>
	VGA display output:	<ul style="list-style-type: none"> <li>• Drives two analog display at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors</li> </ul>

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Maximum Refresh Rates (Hz) by Connection			
	DisplayPort to VGA	DisplayPort to DVI-D	DisplayPort to HDMI	DisplayPort
640 x 480	85	60	60	60
800 x 600	85	60	60	60
1024 x 768	85	60	60	60
1280 x 720	85	60	60	60
1280 x 1024	85	60	60	60
1440 x 900	75	60	60	60
1600 x 1200	60	60	60	60
1680 x 1050	60	60	60	60
1920 x 1080	60-R	60-R	60	60
1920 x 1200	60-R	60-R		60
1920 x 1440				60
2048 x 1536				60
2560 x 1600				60

### Technical Specifications - Graphics

<b>NVIDIA GeForce GT630 Graphics Card</b>		
<b>Introduction</b>	<p>The NVIDIA GeForce GT630 DP (2GB) PCIe x16 Card Graphics Card provides a full height, PCI Express x16 graphics add-in card solution based on the NVIDIA Kepler Architecture GPU. The card is designed to support three display connections through its DVII, and two DisplayPort connectors.</p> <p>An ideal solution for desktop PC customers seeking enhanced 2D and advanced 3D graphics performance, the NVIDIA GeForce GT630 DP (2GB) PCIe x16 Cards are an excellent choice for business users who want run multiple displays from a single graphics board. Engage in Web conferencing or video or photo editing, while improving your everyday business PC experience with better graphics and excellent visual display quality.</p>	
<b>Performance and Features</b>	<p>The NVIDIA GeForce GT630 DP (2GB) PCIe x16 Cards deliver superior PCI Express (PCIe) Gen 3 features including:</p> <ul style="list-style-type: none"> <li>• Unprecedented flexibility for new applications and enhanced performance</li> <li>• Support for NVIDIA surround technology</li> <li>• Run multiple displays from a single graphics card</li> <li>• Full 16 lane PCIe Generation 3 bus support with peak bandwidth support</li> <li>• Wireless Display ready for future support</li> </ul>	
<b>Form Factor</b>	PCIe x16 Card	
<b>Graphics Controller</b>	NVIDIA Kepler Architecture GPU	
<b>Core Clock</b>	875 MHz	
<b>Memory Clock</b>	891 MHz	
<b>Memory Size</b>	2 GB DDR3 128 bit	
<b>Memory Bandwidth</b>	28.5 GB/s	
<b>Display Max. Resolution</b>	2560 x 1600 digital, 2048 x 1536 analog	
<b>Display Support</b>	Integrated 400 MHz RAMDAC	
<b>Supported Display Resolutions and Refresh Rates</b>		
<b>Note:</b> other resolutions may be available but are not recommended as they may not have been tested and qualified by HP		
Resolution	Maximum Refresh Rates (Hz)	
	Analog Connection	Digital Connection
640 x 480	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 1024	85	60
1440 x 900	75	60
1600 x 1200	85	60

### Technical Specifications - Graphics

1680 x 1050	75	60
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	60
2048 x 1536	75	60
2560 x 1600	N/A	60

### NVIDIA NVS 315 1GB PCIe x 16 Graphics Card

<b>Introduction</b>	Get efficient dual-display graphics performance in a PCI Express low-profile graphics card with the NVIDIA NVS 315 PCIe x16 1 GB Graphics Card, an ideal desktop graphics solution for professional business and commercial applications.
<b>Performance and Features</b>	<p>The NVIDIA® NVS 315 Graphics Card offers 1 GB of ultrafast DDR3 memory and is capable of supporting up to 2 displays.</p> <p>DisplayPort connector supports multimode technology to support connection to DVI-D, VGA and HDMI monitors with optional adapters in kits NR078AA, FH973AT, BP937AA, AS615AA.</p> <p>For a DisplayPort to DisplayPort connections use the optional DisplayPort Cable Kit VN567AA.</p>
<b>Form Factor</b>	Low Profile: 2.713 × 6.15 in
<b>Graphics Controller</b>	NVIDIA® NVS 315
<b>Memory Clock</b>	875MHz
<b>Memory Size</b>	512 MB DDR3
<b>Memory Bandwidth</b>	14 GB/s
<b>Connectors</b>	DMS-59 , with support for dual VGA, dual DVI or dual Display Port with the appropriate adapter cable
<b>Display Max. Resolution</b>	Up to 2048 x 1536 VGA; 1920 x 1200 DVI; 2560 x 1600 DisplayPort
<b>Display Output</b>	Up to 2 displays in the following configurations
	<ul style="list-style-type: none"> <li>• Dual DVI :             <ul style="list-style-type: none"> <li>○ Drives two DVI displays using optional HP DMS59 DVI Dual-head Connector Cable DL139A</li> </ul> </li> <li>• Dual DisplayPort :             <ul style="list-style-type: none"> <li>○ Drives two DisplayPort using optional HP DMS-59 to Dual DisplayPort kit XP688AA</li> </ul> </li> <li>• Dual VGA :             <ul style="list-style-type: none"> <li>○ Drives two analog using the included HP DMS-59 to Dual VGA Cable</li> </ul> </li> </ul>
<b>Supported Display Resolutions and Refresh Rates</b>	
<b>Note:</b> other resolutions may be available but are not recommended as they may not have been tested and qualified by HP	

### Technical Specifications - Graphics

Resolution	Maximum Refresh Rates (Hz) by Connection	
	Analog Connection	Digital Connection
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	60
1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	60
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	60*
2560 x 1600	N/A	60*
		* Display Port Only

### AMD Radeon HD 8350 1GB PCIe x16 DH Graphics Card

<b>Introduction</b>	Get stable 2D and advanced 3D graphics performance from the AMD Radeon HD 8350 1 GB PCIe x16 DH Graphics Card, a low profile, PCI Express x16 graphics add-in card based on the AMD Radeon HD 8350 GPU, great for Web conferencing or video and photo editing.
<b>Form Factor</b>	PCIe x16
<b>Graphics Controller</b>	AMD Radeon HD 8350
<b>Core Clock</b>	GPU engine operates at 523 MHz
<b>Memory</b>	1GB, DDR3, SDRAM
<b>Memory Clock</b>	875 MHz
<b>HDCP Support</b>	Yes
<b>Display Max. Resolution</b>	Digital 1920 x 1200 Analog 2048 x 1536

### Technical Specifications - Graphics

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

	Analog Connection	Digital Connection
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	75
1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	75-R
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	N/A
2560 x 1600	N/A	N/A

#### AMD Radeon HD 8490 1GB PCIe x16 Graphics Card

<b>Introduction</b>	Get impressive graphics and high resolution dual-display performance in a low profile, PCI Express x16 graphics add-in card based on the AMD Radeon HD 8490 Graphics Processor. Improve your everyday PC, Web conferencing, and video or photo editing.
<b>Form Factor</b>	PCIe x16
<b>Graphics Controller</b>	AMD Radeon HD 8490
<b>Core Clock</b>	GPU engine operates at 875 MHz
<b>Memory</b>	1GB, DDR3, SDRAM
<b>Memory Clock</b>	900 MHz
<b>HDCP Support</b>	Yes
<b>Display Max. Resolution</b>	Digital 2560 x 1600 Analog 2048 x 1536

### Technical Specifications - Graphics

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

	Analog Connection	Digital Connection
300 x 200	85	60
320 x 240	85	60
400 x 300	85	60
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	75
1600 x 900	85	60
1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	75-R
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	60
2560 x 1600	N/A	60



### Technical Specifications - Hard Disk and Solid State Storage

#### Introduction:

HP Serial Advanced Technology Attachment (SATA) Hard Drives maximize the performance of HP Business PCs by providing the technologies to meet your increasing storage demands with high-capacity drives offering superior reliability and performance.

SATA provides faster data transfer speeds, better system cooling airflow, more bandwidth, more headroom for speed increases in future generations and better data integrity. A next-generation technology, the SATA interface connects hard drives to the PC platform enabling easy aggregation of multiple hard drives into a single PC. This offers you the additional benefits of dedicated bandwidth, the ability to more easily identify device failures and scalability. The HP ProDesk 600 G1 Series Business PC supports the latest SATA 6.0Gb/s specification.

#### HP Drive Lock

HP Serial ATA Hard Drives offer enhanced security via a new Drive Lock. When enabled, this ATA security feature set prevents software access to user data on the drive until one or two user-defined passwords are provided.

#### SMART IV Technology

Self-Monitoring Analysis and Reporting Technology (SMART) hard drive technology allows hard drives to monitor their own health and to raise flags if imminent failures are predicted. If the drive determines that a failure is imminent, the SMART hard drive technology enables the intelligent manageability or management software to generate a fault alert. While the current versions of SMART hard drives do a good job monitoring the data on the hard drive media, the ever increasing emphasis on reliability and quality has promoted HP to implement SMART IV technology which constantly checks that the data flow from host interface to media and media to host interface is not compromised. This is accomplished by inserting a 2 byte parity code into every 512 byte block in the data path of the hard drive's Cache RAM. This unique parity checking performed by HP's SMART IV technology hard drives, allows for more complete error detection coverage encompassing the entire data path between the host and the hard drive.

Smart IV is also known as IOEDC: I/O Error Detection Code.

#### Native Command Queuing

NCQ or Native Command Queuing is a SATA protocol extension that allows the hard drive to have several write or read commands outstanding at the same time. In contrast, normal non-queued operation requires each command to be completed before the next command is issued by the host system. Queuing allows the drive to complete the commands in the order that allows for best overall throughput. It also involves an advanced method of transferring data to or from the host, called First Party Direct Memory Access (FPDMA), which allows the hard drive and the host controller to manage the data transfers for multiple outstanding commands, without involving the host processor. NCQ can contribute to better performance but the results are dependent on many factors, including the access patterns of the various applications and operating system functions that are initiating drive accesses. Enabling NCQ features in the hard drive requires AHCI support from the host system BIOS, controller, and driver. AHCI support is typically implemented in RAID configurations.

**Note:** GB = 1 billion bytes. Actual available capacity is less.

---

#### HP 500-GB 7200 RPM SATA 2.5" Self-Encrypting (SED) Hard Disk Drive

<b>Capacity</b>	500,107,862,016 bytes
<b>Rotational Speed</b>	7,200 rpm

### Technical Specifications - Hard Disk and Solid State Storage

<b>Drive Type</b>	Self-Encrypting Drive (SED) with SATA interface	
<b>Interface</b>	SATA 6 Gb/s	
<b>Segmented Buffer with write cache</b>	32768 KB - A portion of buffer capacity used for firmware	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time</b> (typical reads)	Single Track:	1.0 ms
	Average:	13 ms
	Full-Stroke:	25 ms
<b>Media Diameter</b>	2.5 in/63.5 mm	
<b>Height</b>	0.267 in/6.8 mm, ±0.2mm	
<b>Width</b>	2.75 in/69.85 mm, ±0.25mm	
<b>Length</b>	3.945 in/100.2 mm, ±0.25mm	
<b>Weight</b>	3.35 oz/95 g (max)	
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)	

### HP 500-GB 7200 RPM SATA 2.5" Self-Encrypting (SED) Hard Disk Drive

<b>Capacity</b>	500,107,862,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Drive Type</b>	Self-Encrypting Drive (SED) with SATA interface	
<b>Interface</b>	SATA Interface conforming to Serial ATA International Organization: Serial ATA Revision 2.6	
<b>Segmented Buffer with write cache</b>	32768 KB - A portion of buffer capacity used for firmware	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time</b> (typical reads)	Single Track:	1.0 ms
	Average:	13 ms
	Full-Stroke:	25 ms

### Technical Specifications - Hard Disk and Solid State Storage

<b>Media Diameter</b>	2.5 in/63.5 mm
<b>Height</b>	0.267 in/6.8 mm, $\pm 0.2$ mm
<b>Width</b>	2.75 in/69.85 mm, $\pm 0.25$ mm
<b>Length</b>	3.945 in/100.2 mm, $\pm 0.25$ mm
<b>Weight</b>	3.35 oz/95 g (max)
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)

### HP 1-TB SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)

<b>Formatted Capacity</b>	1 TB	
<b>Spindle Speed</b>	5,400 rpm +/- 0.2%	
<b>Drive Type</b>	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
<b>Interface</b>	Serial ATA (SATA)	
<b>Cache Buffer</b>	64 MB	
<b>NAND Flash Commercial Multilevel Cell (cMLC)</b>	8 GB	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time (typical reads)</b>	Single Track:	2.0 ms
	Average:	12 ms
<b>Height</b>	0.374 +/- .008 in (9.5 +/- 0.2 mm)	
<b>Width</b>	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
<b>Length</b>	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
<b>Weight</b>	0.254 lb/115 g (max)	
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)	

### HP 500 GB SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)

<b>Formatted Capacity</b>	500 GB
<b>Spindle Speed</b>	5,400 rpm +/- 0.2%

### Technical Specifications - Hard Disk and Solid State Storage

<b>Drive Type</b>	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
<b>Interface</b>	Serial ATA (SATA)	
<b>Cache Buffer</b>	64 MB	
<b>NAND Flash Commercial Multilevel Cell (cMLC)</b>	8 GB	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time</b> (typical reads)	Single Track:	2.0 ms
	Average:	12 ms
<b>Height</b>	0.268 +/- .008 in (6.8 +/- 0.2 mm)	
<b>Width</b>	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
<b>Length</b>	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
<b>Weight</b>	0.209 lb/95 g (max)	
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)	

<b>HP 120 GB Solid State Drive</b>		
<b>Unformatted Capacity</b>	120 GB	
<b>Architecture</b>	Multi Level Cell (MLC) NAND Flash with wear leveling 10 channel controller	
<b>Interface</b>	Serial ATA 2.0 (3.0 Gb/s)	
<b>Dimensions (W x H x D)</b>	2.74 x 0.37 x 4 in (6.98 x 0.95 x 10.2 cm)	
<b>Weight</b>	0.18 lb (80 g)	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 250 MB/s
	Sustained Sequential Write:	Up to 70 MB/s
	Random Read:	Up to 35K IOPs
	Random Write:	Up to 6.6K IOPs
<b>Latency</b>	Read:	65-ms
	Write:	85-ms
<b>Power</b>	DC power requirement:	5 VDC 5%-100 mV ripple p-p

### Technical Specifications - Hard Disk and Solid State Storage

	Total power consumption:	0.15W (active); 0.075W (idle)
<b>Useful Drive Life</b>	35TB written, up to 20GB/day for 5 years	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Maximum Wet Bulb Temperature (operating):	84° F (29° C)
	Shock:	1,500 G/0.5-ms
* For solid state disk drives, GB means 1 billion bytes. 128GB is the unformatted capacity of this drive before a portion of the drive is reserved for flash management features. Actual capacity will vary by content		
** The product achieves a mean time between failure (MTBF) based on population statistics not relevant to individual units.		

<b>HP 128 GB Solid State Drive</b>		
<b>Unformatted Capacity</b>	128 GB*	
<b>Architecture</b>	Multi Level Cell (MLC) NAND	
<b>Interface</b>	SATA 6 GB/sec	
<b>Dimensions (W x H x D)</b>	2.75 x 0.276 x 3.96 in (6.985 x 0.7 x 10.05 cm)	
<b>Weight</b>	0.16 lb (73 g)	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 450 MB/ss
	Sustained Sequential Write:	Up to 260 MB/s
	Random Read (4KB):	up to 46K IOPs
	Random Write (4KB):	up to 56K IOPs
<b>Latency</b>	Read:	55ms (TYP)
	Write:	55ms (TYP)
<b>Power</b>	DC power requirement:	Min 4.5 V; Max 5.5 V
	Total power consumption:	160 mW (Active) ; <85 mW; (Idle)
<b>Useful Drive Life</b>	1.2 million device hours**	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity (operating):	5% to 95%
	Shock:	1,500 G/1.0 msec

### Technical Specifications - Hard Disk and Solid State Storage

<b>Regulations</b>	UL, CSA, EN 60950-2000, CISPR Pub 22 Class B, CNS 13438, AS/NZS CISPR 22:2002 Class B, Korea KCC, CE Mark
* For solid state disk drives, GB means 1 billion bytes. 128GB is the unformatted capacity of this drive before a portion of the drive is reserved for flash management features. Actual capacity will vary by content	
** The product achieves a mean time between failure (MTBF) based on population statistics not relevant to individual units.	

#### HP 256 GB SATA 2.5" Self-Encrypting (SED) Solid State Drive

<b>Unformatted Capacity</b>	256,186,209,271 bytes	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with 25nm MLC NAND Flash and SATA interface	
<b>Interface</b>	Serial ATA 2.0 (3.0 Gb/s)	
<b>NAND Flash</b>	25nm MLC NAND Flash	
<b>Height</b>	.275 in/7mm	
<b>Width</b>	2.75 in/69.85 mm	
<b>Length</b>	3.95 in/100.5 mm	
<b>Weight</b>	0.161 lb (73 g)	
<b>Bandwidth Performance</b>	Sustained Sequential 128k Read:	Up to 450 MB/s
	Sustained Sequential 128k Write:	Up to 260 MB/s
	Random 4k Read:	Up to 46K IOPs
	Random 4k Write:	Up to 56K IOPs
<b>Latency</b>	Read:	55 $\mu$ s
	Write:	55 $\mu$ s
<b>Power</b>	SATA power consumption:	160 mW (active average); <85 mW (idle average)
<b>Useful Drive Life</b>	72TB written, up to 40GB/day for 5 years	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/1 ms

#### HP 500-GB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

### Technical Specifications - Hard Disk and Solid State Storage

<b>Capacity</b>	500,107,862,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)	
<b>Buffer Size</b>	16 MB	
<b>Logical Blocks</b>	976,773,168	
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms
<b>Height</b> (nominal)	1 in/2.54 cm	
<b>Width</b> (nominal)	Media diameter: 3.5 in/8.89 cm	
	Physical size: 4 in/10.2 cm	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	

### HP 1-TB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

<b>Capacity</b>	1,000,204,886,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)	
<b>Buffer Size</b>	32 MB	
<b>Logical Blocks</b>	1,953,525,168	
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms
<b>Height</b> (nominal)	1 in/2.54 cm	
<b>Width</b> (nominal)	Media diameter: 3.5 in/8.89 cm	
	Physical size: 4 in/10.2 cm	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	

### Technical Specifications - Hard Disk and Solid State Storage

<b>HP 2-TB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive</b>		
<b>Unformatted Capacity</b>	2 TB	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	SATA 6Gb/s NCQ	
<b>Cache, Multisegmented (MB)</b>	64 MB	
<b>Seek Time (average)</b>	Read	<8.5 ms
	Write	<9.5 ms
<b>Height</b>	1.028 in/26.11 mm	
<b>Width</b>	4.0 in/101.6 mm	
<b>Depth</b>	5.787 in/146.99 mm	
<b>Weight</b>	1.38 lb/626 g	
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)	



### Technical Specifications - Removable Storage

<b>HP Slim SuperMulti DVD Writer Drive</b>		
<b>Height</b>	12.7mm height	
<b>Orientation</b>	Either horizontal or vertical	
<b>Interface type</b>	SATA/ATAPI	
<b>Disc recording capacity</b>	Up to 8.5 GB DL or 4.7 GB standard	
<b>Dimensions (W x H x D)</b>	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel	
<b>Weight (max)</b>	0.42 lb (190 g)	
<b>Write speeds</b>	DVD-RAM	Up to 5X
	DVD-R DL	Up to 6X
	DVD+R	Up to 8X
	DVD+RW	Up to 8X
	DVD+R DL	Up to 6X
	DVD-R	Up to 8X
	DVD-RW	Up to 6X
	CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Read speeds</b>	DVD-RAM	Up to 5X
	DVD-RW, DVD+RW	Up to 8X
	DVD-R DL, DVD+R DL	Up to 8X
	DVD+R, DVD-R	Up to 8X
	DVD-ROM DL, DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Access time</b> (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)
	Stop Time	6 seconds (typical)
<b>Power</b>	Source	Slimline SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, 1600 mA maximum)
<b>Environmental conditions</b> (operating - non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature	84° F (29° C)

### Technical Specifications - Removable Storage

<b>HP Slim Blu-ray BDXL Drive</b>			
<b>Height</b>	12.7mm height		
<b>Orientation</b>	Either horizontal or vertical		
<b>Interface type</b>	SATA/ATAPI		
<b>Disc recording capacity</b>	Up to 128 GB QL, 100 GB TL, 50 GB DL or 25 GB standard SL		
<b>Dimensions (W x H x D)</b>	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel		
<b>Weight (max)</b>	Up to 0.37 lb (170 g) without bezel		
		<b>Triple-layer</b>	<b>Quadruple-layer</b>
<b>Write speeds</b>	BD-R	Up to 4X	Up to 4X
	BD-RE	Up to 2X	Not supported
		<b>Single-layer</b>	<b>Double-layer</b>
	BD-R	Up to 6X	Up to 6X
	BD-RE	Up to 2X	Up to 2X
	DVD-R	Up to 8X	Up to 6X
	DVD-RW	Up to 6X	Not supported
	DVD+R	Up to 8X	Up to 6X
	DVD+RW	Up to 8X	Not supported
	DVD-RAM	Up to 5X	
	CD-R	Up to 24X	
	CD-RW	Up to 24X	
		<b>Triple-layer</b>	<b>Quadruple-layer</b>
	BD-R	Up to 4X	Up to 4X
	BD-RE	Up to 4X	Not supported
		<b>Single-layer</b>	<b>Double-layer</b>
BD-ROM	Up to 6X	Up to 6X	
BD-R	Up to 6X	Up to 6X	
<b>Read speeds</b>	BD-RE	Up to 6X	Up to 6X
	DVD-ROM	Up to 8X	Up to 8X
	DVD-R	Up to 8X	Up to 8X
	DVD-RW	Up to 8X	
	DVD+R	Up to 8X	Up to 8X

### Technical Specifications - Removable Storage

	DVD+RW	Up to 8X	
	BDMV (AACs Compliant Disc)	Up to 6X/2X (Read/Play)	
	DVD-RAM	Up to 5X	
	DVD-Video (CSS Compliant Disc)	Up to 8X/4X (Read/Play)	
	CD-R/RW/ROM	Up to 24X	
	CD-DA(DAE)	Up to 20X/10X (Read/Play)	
<b>Access time</b> (typical reads, including settling)	Random	BD-ROM: 205 ms (typical), DVD-ROM: 185 ms (typical), CD-ROM: 165 ms (typical)	
	Full Stroke	BD-ROM: 350 ms (typical), DVD-ROM: 345 ms (typical), CD-ROM: 340 ms (typical)	
<b>Power</b>	Source	Slimline SATA DC power receptacle	
	DC Power Requirement	5 VDC $\pm$ 5%-100 mV ripple p-p	
	DC Current	5 VDC -1200 mA typical, 2000 mA maximum	
<b>Environmental conditions</b> (operating - non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Relative Humidity	10% to 80%	
	Maximum Wet Bulb Temperature	84° F (29° C)	

### HP Slim DVD-ROM Drive

<b>Height</b>	12.7mm		
<b>Orientation</b>	Either horizontal or vertical		
<b>Interface type</b>	SATA/ATAPI		
<b>Dimensions (W x H x D)</b>	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel		
<b>Weight (max)</b>	Up to 0.37 lb (170 g) without bezel		
<b>Read speeds</b>	DVD+R/-R/+RW/-RW/+R DL /-R DL	Up to 8X	
	DVD-ROM	Up to 8X	
	CD-ROM, CD-R	Up to 24X	
	CD-RW	Up to 24X	
<b>Access time</b> (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)	
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)	
<b>Power</b>	Source	Slimline SATA DC power receptacle	
	DC Power Requirement	5 VDC $\pm$ 5%-100 mV ripple p-p	
	DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum	

### Technical Specifications - Removable Storage

<b>Environmental</b> (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature (operating)	84° F (29° C)

### Technical Specifications – Memory

#### System Memory Support

The HP ProDesk 600 G1 Business PC supports the 4<sup>th</sup> generation Intel® Core™ processor family. Based on a new PC micro-architecture, the processor is designed for a two-chip platform consisting of a processor and Platform Controller Hub (PCH). Unlike previous generations, the 4<sup>th</sup> generation Intel® Core™ processor includes an Integrated Memory Controller (IMC). The IMC supports DDR3/DDR3L protocols with two independent, 64-bit wide channels each accessing one or two DIMMs.

- Two channels of non-ECC DDR3/DDR3L unbuffered dual in-line memory modules (UDIMM) with a maximum of two DIMMs per channel
- Single-channel and dual-channel memory organization modes
- Data burst length of eight for all memory organization modes
- Memory data transfer rates of up to 1600 MT/s; actual supported data transfer rate determined by the configured processor.
- 64-bit wide channels
- DDR3/DDR3L system memory I/O voltage of 1.5V
- Theoretical maximum memory bandwidth of:
  - 21.3 GB/s in dual-channel mode assuming 1333 MT/s
  - 25.6 GB/s in dual-channel mode assuming 1600 MT/s

#### Platform Memory Support

- The Small Form Factor (SFF) and Tower (TWR) platforms support up to four (4) industry-standard DDR3-SDRAM DIMMs.
- The Desktop Mini platform supports up to two (2) industry-standard DDR3-SDRAM SODIMMs.

**CAUTION:** You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

**NOTE:** For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

### Technical Specifications – Networking and Communications

<b>Intel® I217LM GbE Network Connection (integrated)</b>		
<b>Connector</b>	RJ-45	
<b>System Interface</b>	Integrated on PCA	
<b>Controller</b>	Intel I217LM GbE platform LAN connect networking controller	
<b>Memory</b>	24 KB FIFO packet buffer memory	
<b>Data rates supported</b>	10/100/1000 Mbps	
<b>IEEE Compliance</b>	802.1P 802.1Q 802.2 802.3 802.3ab 802.3az 802.3u	
<b>Bus architecture</b>	PCI Express and SMBus	
<b>Data transfer mode</b>	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)	
<b>Power requirement</b>	Requires 3.3V and 0.9V or just 3.3V with integrated regulators Power consumption 0.733 Watts	
<b>Boot ROM support</b>	Yes	
<b>Network transfer mode</b>	Full-duplex	
	Half-duplex (not supported for the 1000BASE-T transceiver)	
<b>Network transfer rate</b>	10BASE-T (half-duplex) 10 Mbps	
	10BASE-T (full-duplex) 20 Mbps	
	100BASE-TX (half-duplex) 100 Mbps	
	100BASE-TX (full-duplex) 200 Mbps	
	1000BASE-T (full-duplex) 2000 Mbps	
<b>Environmental</b>	Operating Temperature:	0° to 85° C
	Operating Humidity:	60% RH
<b>Management</b>	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostic	
<b>Alerting</b>	ASF 2.0 support; AMT 9.0 support	

### Technical Specifications – Networking and Communications

<b>Intel® Ethernet I210-T1 Gigabit Network Adapter</b>		
<b>Connector</b>	RJ-45	
<b>System Interface</b>	PCI Express x1	
<b>Controller</b>	Intel® I210 Gigabit Ethernet Controller	
<b>Memory</b>	Integrated Dual 48K configurable transmit receive FIFO Buffers	
<b>Data rates supported</b>	10/100/1000 Mbps	
<b>IEEE Compliance</b>	802.1P 802.1Q 802.2 802.3 802.3AB 802.3u 802.3x flow control	
<b>Bus architecture</b>	PCI-E 2.1	
<b>Data path width</b>	X1, 250 MB/s, Bi-directional interface	
<b>Data transfer mode</b>	Bus-master DMA	
<b>Hardware certifications</b>	FCC, B, CE, TUV-c, TUVus Mark Canada and United States, TUV-GS Mark for European Union	
<b>Power requirement</b>	Aux 3.3 V, 3.0 Watts in 1000 base-T and 1.0 Watts in 100 Base-T	
<b>Boot ROM support</b>	Yes 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps	
<b>Network transfer rate</b>	10BASE-T (half-duplex) 10 Mbps	
	10BASE-T (full-duplex) 20 Mbps	
	100BASE-TX (half-duplex) 100 Mbps	
	100BASE-TX (full-duplex) 200 Mbps	
	1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI bus)	
<b>Environmental</b>	Operating Temperature:	32° to 132° F (0° to 55° C )
	Operating Humidity:	85% at 131° F (55° C)
<b>Management</b>	WOL, PXE, DMI, WFM 2.0	
<b>Intel Centrino Advance-N 6205 Wireless Network Interface Connection</b>		

### Technical Specifications – Networking and Communications

<b>Wireless LAN Standards</b>	IEEE 802.11a/b/g/n
	IEEE 802.11 e, 802.11i, 802.11d, 802.11d, 802.11h
<b>Interoperability</b>	Wi-Fi certified (802.11 a/b/g/n WMM, WPA, WPA2 and WPS)
	Tested with wireless access points from several major manufacturers
	OS compatible with Microsoft Windows, Win7 and XP
	Cisco Compatible Extensions Program compliant (802.11a/b/g only) with Microsoft Windows XP and Windows 7
<b>Frequency Band</b>	2.4 GHz and 5 GHz
<b>Antenna Structure</b>	2 transmit; 2 receive (2x2)
<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps
	802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11n: 66 possible data rates, ranging from 6 Mbps to 300 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
<b>Security</b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES (support for key sizes of 128bits), TKIP, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP, MSCHAP, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM, EAP-AKA PAP, CHAP, TLS, GTC
	Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4) with Microsoft Windows XP only.
<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required) Intel® My Wifi Technology (iPAN)
<b>Roaming</b>	Provide seamless roaming between like access points (same frequency band)
<b>Output Power (for CCK)</b>	15 dBm
<b>Output Power (for OFDM; power varies by data rate)</b>	15 dBm
<b>Power Consumption</b>	Transmit: 2.3 Watts (average, with one spatial streams)
	Receive: 1.9 Watts (average with two receive chains)
	Idle mode: 30mW – 40mW (average)
	Radio off: 20 mW (max)
<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode



### Technical Specifications – Networking and Communications

<b>Antenna Connections</b>	3 U.FL type connectors, 50 ohm nominal impedance	
<b>Range</b>	802.11 a - Typical (@6 Mbps)	600 feet - Outdoor Open Area 150 feet - Indoor, Office environment
	802.11 b - Typical (@1 Mbps)	1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment
	802.11 g - Typical (@1 Mbps)	1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment
<b>Form Factors</b>	Tower & SFF:	PCIe
<b>Weight</b>	0.013 lb (4.0 g)	
<b>Dimensions</b>	1.1 x 1.2 in (26.8 x 30.0 mm)	
<b>Operating Voltage</b>	3.3V +/- 9%, 1.5V +/- 5%	
<b>Temperature</b>	<b>Operating:</b> <b>Non-operating:</b>	32° to 176° F (0° to 80° C) -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating:</b> <b>Non-operating:</b>	10% to 90% (non-condensing) 5% to 90% (non-condensing)
	Microsoft Windows XP	Microsoft Windows Win 7
<b>Configuration Utility</b>	<ul style="list-style-type: none"> <li>Microsoft Windows XP Wireless Network Connection Manager</li> <li>Intel PROSet for Microsoft Windows XP (required for Cisco Compatible Extensions support)</li> </ul>	Intel IHV extensions for Win7 available to support Cisco Compatible Extensions

### Technical Specifications - Audio

<b>High Definition Audio</b>	
<b>Type</b>	Integrated
<b>HD Stereo Codec</b>	Realtek 2-channel ALC221 codec
<b>Audio I/O Ports</b>	Front microphone-In (150-K ohm Input Impedance)
	Rear Line-In/Microphone input (150-K ohm Input Impedance, function is configurable by audio driver)
	Rear Line-Out* (190 ohms Output Impedance, expects at least a 10-K ohm load)
	Front Headphone-Out (0.5 Ohm Output Impedance, expects at least a 32 ohm load) Front Microphone/Headphone jack is re-task able to provide Microphone input, line-in or Headphone output to support connecting two headphones to the front of the system. When configured as a second front headphone output, both front headphone outputs are always driven with the same signal.
	All ports are 3.5mm
<b>Internal Speaker Amplifier</b>	1.5W amplifier for the internal speaker only. External speakers must be powered externally. Rear Line-in audio port is re-taskable as either Line-in or Microphone-In.
<b>Multi-streaming Capable</b>	Multi-streaming can be enabled in the Realtek control panel to allow independent audio streams to be sent to/from the front and rear jacks.
<b>Sampling</b>	8 kHz - 192 kHz
<b>Wavetable Syntheses</b>	Yes – Uses OS soft wavetable
<b>Analog Audio</b>	Yes
<b># of Channels on Line-Out</b>	Stereo (Left & Right channels)
<b>Internal Speaker</b>	Yes
<b>External Speaker Jack</b>	Yes

### Technical Specifications - Input/Output Devices

<b>HP USB Keyboard</b>		
<b>Physical characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	18.12 x 6.47 x 0.96 in (46.03 x 16.43 x 2.44 cm)
	Weight	2 lb (0.9 kg)
<b>Electrical</b>	Operating voltage	+ 5VDC ± 5%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration

### Technical Specifications - Input/Output Devices

	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	30 in (76.2 cm) on concrete, 16-drop sequence
<b>Approvals</b>	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	
<b>Kit contents</b>	Keyboard	Installation Guide
	Warranty Card	Safety and Comfort Guide

### HP PS/2 Keyboard

<b>Physical Characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	18.22 x 6.47 x 1.1 in (46.28 x 16.43 x 2.79 cm)
	Weight	2 lb (0.9 kg) minimum
<b>Electrical</b>	Operating voltage	+ 5VDC $\pm$ 10%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	PS/2 6-pin mini din connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	50-dBA maximum sound pressure level

### Technical Specifications - Input/Output Devices

	Operating temperature	32° to 104° F (0° to 40° C)
	Non-operating temperature	-22° to 149° F (-30° to 65° C)
	Operating humidity	15% to 80% (non-condensing at ambient)
	Non-operating humidity	15% to 90% (non-condensing at ambient)
	Operating shock	N/A
	Non-operating shock	65 inch 2.9 ms, six surface; 30g 266 inch/second; 50g 266 inch/second six surface
	Operating vibration	2-g peak acceleration
	Non-operating vibration	Starting at 5 Hz, vary the frequency of vibration from 5 to 500 Hz and back to 5 Hz at a Logarithmic sweep rate of 1 octave per minute.
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	29.93 in (76 cm) on concrete, 16-drop sequence
<b>Approvals</b>	CUL, ICES-003 Class B, FCC, CE Mark, TUV GS, VCCI, BSMI, C-Tick, KC	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	

### HP USB Smart Card (CCID) Keyboard

<b>Key Benefits:</b>	<ul style="list-style-type: none"> <li>Protects against unauthorized access with smart card technology</li> <li>Delivers even greater security when combined with a HP ProtectTools smart card and the HP ProtectTools Security Software</li> <li>Combination of username and password or pin with a smart card or security token</li> <li>Secures online transactions using digital signatures and certificates</li> <li>Conforms to industry standards for ease of setup and use</li> <li>Delivers long product life and quiet operation with high-impact materials and lubricated keys</li> <li>Spill drain feature</li> </ul>	
<b>Physical Characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Form factor	USB basic smart card keyboard
	Colors	Carbonite/Silver
	Dimensions (H x W x D)	18.2 x 6.3 x 1.3 in (46.3 x 16.1 x 3.3 cm)

### Technical Specifications - Input/Output Devices

	Weight	2 lb (0.9 kg) minimum
<b>Electrical</b>	Operating voltage	+ 5VDC $\pm$ 5%
	Power consumption	100-mA maximum (with four LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Languages	30+ available
	Keycaps	Standard design
	Switch actuation	55 g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence

### Technical Specifications - Input/Output Devices

<b>SmartCard Function</b>	Support	All ISO 7816 smart cards		
	Interface	Reads from and writes to all ISO7816-1, 2, 3, 4 memory and microprocessor smart cards (T=0, T=1)		
	Chipset	SCM STCII		
	Standard APIs supported	PC/SC, EMV2000, SET		
	Power	USB Port		
		Short circuit detection (protects smart card and reader)		
		Power supply compliant with ISO7816 and EMV (5V, 60 mA)		
		Supports 3-V and 5-V cards		
	Power consumption	100-mA maximum draw		
	Communication	From card	9600 bps to 330,000 bps	
		From computer	12 Mbps (USB transfer speed)	
	Landing mechanism	Contact device	Friction contact	
		Card insertions rating	Up to 100,000 insertion cycles	
	Interface modes	CCID protocol		
Reader performance interface	USB connection			
Electro-magnetic standards	Europe	2004/108/EC		
	USA	USAFCC part 15		
<b>Approvals</b>	CE-Mark, UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC, EMV2000, USB-IF			
<b>Ergonomic Compliance</b>	ISO 9241-4, TUVGS			
<b>Kit Contents</b>	Keyboard, I/O Security and Documentation CD, warranty card			

### HP USB PS/2 Washable Keyboard

<b>Physical Characteristics</b>	Keys	104 (US) Layout, 105 (EU) layout – depending upon country
	Dimensions (L x W x H)	17.67x 6.62 x 1.38 in (449 x 168 x 35 mm)
	Weight	1.7 lb (0.77 kg) minimum

### Technical Specifications - Input/Output Devices

<b>Electrical</b>	Operating voltage	+ 5VDC $\pm$ 5%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Keycaps	Stepped -profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	7 ft (2.2 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
<b>Environmental</b>	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	4° to 149° F (-20° to 65° C)
	Operating humidity	10% to 95% (non-condensing at ambient)
	Non-operating humidity	0% to 95% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
<b>Operating system support</b>	Windows® 7, Windows Vista, Windows XP Professional	
<b>Approvals</b>	UL, cUL, FCC, CE, TUV GS, VCCI, BSMI, C-Tick, KCC, USB-IF, WHQL, EN/IEC 60601-1, IP66/NEMA4X	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	

### HP Wireless Keyboard and Mouse

<b>Keyboard</b>	Dimensions (H x L x W)	1.09 x 18.1 x 6.47 in (27.87 x 460.3 x 164.3 mm)
	Weight – Without Two AA Alkaline Batteries	1.94 lb (880 g)
<b>Mouse</b>	Dimensions (H x L x W)	1.46 x 4.53 x 2.47 in (37 x 115 x 62.9 mm)



### Technical Specifications - Input/Output Devices

	Weight – Without Two AA Alkaline Batteries	0.15 lb (67 g)
<b>Receiver</b>	Dimensions (H x L x W)	0.33x 1.79 x 0.72 in (8.4 x 45.5 x 18.4 mm)
	Weight	0.21 oz (5.9 g)
	Range	32.8 ft (10 m)
<b>System Requirements</b>	<p>Windows 10, Windows 8, Windows 7 Professional Edition 32*, Windows 7 Professional Edition 64*, Windows Vista or Windows XP</p> <p>Available USB port for the receiver</p> <p>CD-ROM Drive</p> <p>* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows functionality. See <a href="http://www.microsoft.com">http://www.microsoft.com</a>.</p>	
<b>Approvals</b>	Product Safety	UL; CSA /TUV (Europe only); CE Mark; CB Report
	Ergonomics	ANSI; ISO (Europe only); GS Mark (Germany only)
	EMC	FCC; CE; ACA (-tick); BSMI; KC ; VCCI
	CE Mark	EN 55022:2010; EN 55024; EN 301489-1; EN 61000
	Design Guidelines for PCs	PC 99 – connector overmold colors; PC 2001 – full functionality
	Telecom	All local telecom requirements and approvals for intended markets
	USA	FCC Title 47 CFR, Par 15, Subpart C; other local requirements
	Country Support	US, Belgium, Switzerland, Spain, Denmark, Netherlands, France, Germany, Italy, Portugal, Sweden, Norway, Finland, UK, Poland, Czech Republic, Turkey, Greece, Austria, Bulgaria, Cyprus, Estonia, Hungary, Ireland, Latvia, Lithuania, Luxemburg, Malta, Romania, Slovakia, Slovenia, Vietnam, HK, Australia, NZ, Malaysia, Singapore, Indonesia, Philippines, Thailand, Canada, China, Japan, Korea, Taiwan, India, Venezuela, Ecuador, Russia, Ukraine, Israel, Croatia, United Arab Emirates, Peru, Brazil, Chile, Argentina, Mexico, South Africa, and up to 193 countries worldwide.
<b>Environmental</b>	Keyboard contains 25% post-consumer recycled plastic material	
<b>Encryption</b>	128bit AES Encryption	

### Technical Specifications - Input/Output Devices

<b>HP PS/2 Mouse</b>		
<b>Dimensions</b> (H x L x W)	1.46 x 2.48 x 4.53 in (3.70 x 6.29 x 11.50 cm)	
<b>Weight</b>	3.53 oz (100g; +10g/- 5 g)	
<b>Environmental</b>	Operating temperature	-32° to 104°F (0° to 40° C)
	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non condensing at ambient)
	Non-operating humidity	10% to 90% (non condensing at ambient)
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
<b>Electrical</b>	Operating voltage	5 VDC ± 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector
	ESD	CE level 4, 15 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
<b>Mechanical</b>	Resolution	800 DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
	Acceleration	±15%
	Switch actuation	65±20 gf

### Technical Specifications - Input/Output Devices

	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	80 km
	Cable length	6 ft (1.8 m)
	Microsoft PC99 - 2001	Mechanically compliant
<b>Scroll wheel</b>	Width	6 mm
	Diameter	22.5 ± 0.2 mm
	Maximum rotation force	50 gf-cm
	Switch type	Light force micro-switch
	Switch life	1 million operations
	Mechanical life	Minimum 200,000 revolutions
<b>Regulatory Approvals</b>	UL/cUL, FCC, CE Mark, TUV/GS, VCCI, KCC, BSMI, C-Tick	

### HP USB Mouse

<b>Dimensions</b> (H x L x W)	1.5 x 4.5 x 2.5 in (3.7 x 11.5 x 6.3 cm)
<b>Weight</b>	0.22 lb (0.10 kg)
<b>Cable length</b>	70.9 in (180 cm)
<b>System requirements</b>	Available USB port

### HP USB 1000dpi Laser Mouse

<b>Dimensions</b> (H x L x W)	1.47 x 4.53 x 2.47 in (37.3 x 114.97 x 62.86 mm)	
<b>Weight</b>	3.360 oz (102g)	
<b>Cable length</b>	70.9 in (180 cm)	
<b>System requirements</b>	Available USB port	
<b>Environmental</b>	Operating Temperature	32° to 104° F (0° to 40° C)

### Technical Specifications - Input/Output Devices

	Non-operating Temperature	-4° to 140° F (-20° to 60° C)
	Operating Humidity	10% to 90% (non-condensing at ambient)
<b>Mechanical</b>	Resolution	1000dpi
	Tracking Speed	45 cm/sec
	Cable Length	70.9 in (180 cm)

### HP USB PS/2 Washable Mouse

<b>Dimensions</b> (H x L x W)	1.56 x 2.44 x 4.61 in (3.95 x 6.21 x 11.7 cm)	
<b>Weight</b>	4.44 oz (126 g)	
<b>Environmental</b>	Operating temperature	-32° to 104°F (0° to 40° C)
	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	10% to 90% non-condensing
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
<b>Electrical</b>	Operating voltage	5 VDC ± 10%
	Power consumption	100mA

### Technical Specifications - Input/Output Devices

	System consumption	PS/2 mini-din connector or USB
	ESD	CE level 2 8 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
<b>Mechanical</b>	Resolution	1000 ± 20% DPI
	Tracking speed	14 in/s ( 35.56 cm/s) maximum
	Acceleration	2 g
	Switch actuation	70 g nominal peak force
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	8.8 ft total 70 cm+ 2m extension
	Cable length	Mechanically compliant
	Microsoft PC99 - 2001	1000 ± 20% DPI
<b>Scroll wheel</b>	Width	6 mm
	Diameter	1 in (25.4 mm)
	Maximum rotation force	48 rats/sec
	Switch type	Light force micro-switch
	Switch life	3 million operations
	Mechanical life	Minimum 200,000 revolutions
<b>Regulatory Approvals</b>	FCC, CE Mark, ICES-003-B, IP66/NEMA4X	

### Technical Specifications – Power

#### Unit Environment and Operating Conditions

##### General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's re-circulated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating: 50° to 95° F (10° to 35° C)* Non-operating: -22° to 140° F(-30° to 60° C)
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 5% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating: 10,000 ft (3048 m) Non-operating: 30,000 ft (9144 m)

\*Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

Power Supply	DM	SFF	TWR
Standard Efficiency	65W active PFC 87% efficient 89% average efficiency at 230V 88% average efficiency at 115V N/A	240W active PFC  240W active PFC	320W active PFC  320W active PFC
80 PLUS Gold	N/A	87/90/87% efficient at 20/50/100% load (115V)  89/91/90% efficient at 20/50/100% load (230V) 240W active PFC	87/90/87% efficient at 20/50/100% load (115V)  89/92/90% efficient at 20/50/100% load (230V) 320W active PFC
80 PLUS Platinum		90/92/89% efficient at 20/50/100% load (115V)  90/93/91% efficient at 20/50/100% load (230V)	90/92/89% efficient at 20/50/100% load (115V)  90/94/91% efficient at 20/50/100% load (230V)
Operating Voltage Range	90 - 264 VAC	90 - 264 VAC	90 - 264 VAC
Rated Voltage Range	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Rated Line Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Operating Line Frequency Range	47 - 63 Hz	47 - 63 Hz	47 - 63 Hz
Rated Input Current	N/A	4A	5.5A

### Technical Specifications – Power

Rated Input Current with Energy Efficient* Power Supply	TBA	4A	5.5A
DC Output	+19.5V		
Current Leakage (NFPA 99: 2102)	<p>Less than 500 microamps of leakage current at 120 Vac with the ground wire disconnected, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.</p> <p>Less than 100 microamps of leakage current at 120 Vac with the ground wire intact with normal polarity, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.</p>		
Power Supply Fan	N/A	N/A	92=>70mm variable speed
Power cord length	N/A	6.0 ft. (1.83 m)	6.0 ft. (1.83 m)
External Power Adapter			
<ul style="list-style-type: none"> <li>Dimensions</li> <li>Total Cord Length</li> </ul>			<p>2.</p> <p>5.</p> <p>1.</p>

### Technical Specifications – Weights & Dimensions

#### Weights & Dimensions

(configured with 1 HDD & 1 ODD; DM configured with 1 HDD only)

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>
Chassis (W x H x D)	6.9 x 1.3 x 7.0 in 175 x 34 x 177 mm	13.3 x 3.95 x 14.9 in 338 x 100 x 379 mm	6.7 x 15.7 x 17.4 in 170 x 399 x 442 mm
System Volume	62.79 cu in 1.05 L	782.7 cu in 12.8 L	1828 cu in 30 L
System Weight	2.9 lb 1.3 kg	16.7 lb 7.6 kg	20.5 lb 9.3 kg
Max Supported Weight (desktop orientation)	N/A	77.0 lb 35.0 kg	77.0 lb 35.0 kg
Tower Stand	<i>Pending</i>	1.1 x 7.0 x 7.9 in 29 x 178 x 200 mm	N/A
Packaging	<i>Pending</i>	9.0 x 19.7 x 23.4 in 229 x 500 x 594 mm	11.6 x 19.7 x 23.2 in 295 x 500 x 590 mm
Shipping Weight	<i>Pending</i>	17.9 lb 8.1 kg	28.8 lb 13.1 kg
Palletization Profile	<i>Pending</i>	4-units per layer 10-layer max. 40-units per pallet	4-units per layer 8-layer max. 32-units per pallet



### Technical Specifications – Miscellaneous Features

#### Management Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- Intel Wired for Management support; industry wide initiative to make Intel architecture based PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

#### Serviceability Features

- Dual colored power LED on front of computer to indicate either normal or fault condition
- Diagnostic LED Explanation Table:
  - Number of 1-second red LED blinks followed by a 2-second pause, then repeats:
    - 2 - processor thermal protection activated
    - 3 - processor not installed
    - 4 - power supply failure
    - 5 -- memory error
    - 6 - video error
    - 7 - PCA failure (ROM detected failure prior to video)
    - 8 - invalid ROM, bootblock recovery mode
    - 9 - system not fetching code
    - 10 - system hang while loading an option ROM
- HP PC Hardware Diagnostics UEFI:
  - This utility enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support
- System/Emergency ROM
- Flash ROM
- CMOS Battery Holder for easy replacement
- Flash Recovery with Video Configuration Record Software
- 5 Aux Power LED on System PCA
- Processor ZIF Socket for easy Upgrade
- Over-Temp Warning on Screen (Requires IM Agents)
- Clear Password Jumper
- DIMM Connectors for easy Upgrade
- Clear CMOS Button
- NIC LEDs (integrated) (Green & Amber)
- Dual Color Power and HD LED - To Indicate Normal Operations and Fault Conditions
- Color coordinated cables and connectors
- Tool-less Hood Removal
- Front power switch
- System memory can be upgraded without removing the system board or any internal components
- Tool-less Hard Drive, CD & Diskette Removal
- Green Pull Tabs, and Quick Release Latches for easy Identification

#### Additional Features

	Description
<b>Towerable Orientation</b>	Product can be oriented as either a desktop or a tower
<b>Drive Lock</b>	Implementation of the industry standard ATA Security feature set. When enabled, it prevents software access to user data on the drive until one or two user-defined passwords are provided.
<b>Drive Protection System</b>	DPS Access through F10 Setup during Boot

### Technical Specifications – Miscellaneous Features

	<p>A diagnostic hard drive self test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user</p> <p>Running independently of the operating system, it can be accessed through a Windows-based diagnostics utility or through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced</p> <p>The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures</p>
<b>SMART Technology (Self-Monitoring, Analysis and Reporting Technology)</b>	Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted
<b>SMART I - Drive Failure Prediction</b>	Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count
<b>SMART II - Off-Line Data Collection</b>	By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure
<b>SMART III - Off-Line Read Scanning with Defect Reallocation</b>	IOEDC: I/O Error Detection Circuitry Detects errors in Read/Write buffers on HDD cache RAM
<b>SMART IV - End-to-End CRC for hard drives</b>	Interface in F10 setup provides confirmation of SMART IV support.

### Technical Specifications – Environmental Data

#### Environmental Data

##### Eco-Label Certifications & Declarations

This product series has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- US ENERGY STAR®
- IT ECO declaration
- EPEAT® Gold where HP registers commercial desktop products. See [epeat.net](http://epeat.net) for registration status in your country.

Model	Energy Consumption (typically configured)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
<b>DM</b>	Normal Operation (Short idle)	8.10 W	8.19 W	7.85 W
	Normal Operation (Long idle)	5.99 W	6.16 W	5.96 W
	Sleep	1.67 W	1.57 W	1.65 W
	Off	1.03 W	1.0 W	1.06 W
<b>SFF</b>	Normal Operation (Short idle)	16.44 W	16.22 W	16.12 W
	Normal Operation (Long idle)	14.15 W	13.19 W	14.80 W
	Sleep	1.44 W	1.52 W	1.43 W
	Off	0.58 W	0.64 W	0.57 W
<b>TOWER</b>	Normal Operation (Short idle)	18.28 W	19.36 W	18.83 W
	Normal Operation (Long idle)	17.94 W	16.83 W	17.79 W
	Sleep	1.47 W	1.57 W	1.46 W
	Off	0.54 W	0.63 W	0.53 W

Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP personal computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Model	Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
<b>DM</b>	Normal Operation (Short idle)	28 BTU/hr	28 BTU/hr	27 BTU/hr
	Normal Operation (Long idle)	20 BTU/hr	21 BTU/hr	20 BTU/hr
	Sleep	6 BTU/hr	5 BTU/hr	6 BTU/hr
	Off	4 BTU/hr	3 BTU/hr	4 BTU/hr
<b>SFF</b>	Normal Operation (Short idle)	56 BTU/hr	55 BTU/hr	55 BTU/hr
	Normal Operation (Long idle)	48 BTU/hr	45 BTU/hr	50 BTU/hr
	Sleep	5 BTU/hr	5 BTU/hr	5 BTU/hr
	Off	2 BTU/hr	2 BTU/hr	2 BTU/hr
<b>TOWER</b>	Normal Operation (Short idle)	63 BTU/hr	66 BTU/hr	64 BTU/hr
	Normal Operation (Long idle)	61 BTU/hr	58 BTU/hr	61 BTU/hr

### Technical Specifications – Environmental Data

Sleep	5 BTU/hr	5 BTU/hr	5 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

\*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

### System Configuration

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)	
<b>Model</b>	(Typically configured)		
<b>DM</b>	Idle	<i>Pending</i>	<i>Pending</i>
	Fixed Disk (random writes)	<i>Pending</i>	<i>Pending</i>
<b>SFF</b>	Idle	3.6	26
	Fixed Disk (random writes)	3.6	26
<b>TOWER</b>	Idle	3.6	26
	Fixed Disk (random writes)	3.6	26

**Spare Part Support** Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

**Batteries** The battery in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 1ppm by weight
- Cadmium greater than 20ppm by weight

	Battery Size	CR2032 (coin cell)
	Battery Type	Lithium
Model	Additional Information	
<b>DM</b>	<ul style="list-style-type: none"> <li>• <i>Pending</i></li> </ul>	
<b>SFF</b>	<ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold where HP registers commercial desktop products. See <a href="http://epeat.net">epeat.net</a> for registration status in your country.</li> <li>• Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</li> <li>• This product contains 14.8% post consumer recycled plastic (by wt.)</li> <li>• This product is 94.1% recyclable when properly disposed of at end of life.</li> </ul>	

### Packaging Materials

### Technical Specifications – Environmental Data

- External:
  - PAPER/Corrugated 2300 g
- Internal:
  - PLASTIC/EPE-Expanded Polyethylene 110 g
  - PLASTIC/Polyethylene low density 56 g
  - PLASTIC/Polypropylene 15 g
- The PAPER/Corrugated material contains at least 38.38% recycled content.
- The PLASTIC/EPE-Expanded Polyethylene material contains at least 60.4% recycled content.
- The PLASTIC/Polyethylene low density material contains at least 60.4% recycled content.
- The PLASTIC/Polyethylene packaging material contains at least 60.4 % recycled content.

### TOWER

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold where HP registers commercial desktop products. See [epeat.net](http://epeat.net) for registration status in your country.
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 15% post consumer recycled plastic (by wt.)
- This product is 95.5% recyclable when properly disposed of at end of life.

### Packaging Materials

- External:
  - PAPER/Corrugated 2280 g
- Internal:
  - PLASTIC/EPE (Expanded Polystyrene) 144 g
  - PLASTIC/Polyethylene low density 40 g
  - PLASTIC/Polypropylene 15 g
- The PAPER/Corrugated material contains at least 53.5% recycled content.
- The PLASTIC/EPE (Expanded Polystyrene) material contains at least 60.42% recycled content.
- The PLASTIC/Polyethylene low density material contains at least 60.42% recycled content.
- The PLASTIC/Polypropylene material contains at least 60.42% recycled content.

### RoHS Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at:

[hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde

### Technical Specifications – Environmental Data

- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

### Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: [hp.com/go/reuse-recycle](http://hp.com/go/reuse-recycle) or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: [hp.com/go/recyclers](http://hp.com/go/recyclers). These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

### Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

[hp.com/hpinfo/globalcitizenship/qcreport/index.html](http://hp.com/hpinfo/globalcitizenship/qcreport/index.html)

Eco-label certifications

[hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html](http://hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html)

ISO 14001 certificates:

[hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html](http://hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html)

After-Market Options (availability may vary by region)

### Communication Devices

	DM	SFF/TWR	Part Number
Intel Ethernet I210 – T1 Gbe NIC		X	E0X95AA
Intel 6205 802.11 a/b/g/n PCIe x1 NIC		X	E0X93AA

**Note:** The use of any of these optional NIC Cards (wired or wireless) will disable the Intel vPro Technology features.

### Graphics Solutions

	DM	SFF/TWR	Part Number
AMD Radeon HD 8350 Graphics (PCIe x16)		X	E1C63AA
AMD Radeon HD 8490 Graphics Card		X	E1C64AA
Nvidia NVS 310 Graphics (PCIe x16)		X	A7U59AA
Nvidia NVS 315 Graphics (PCIe x16)		X	E1C65AA
HP USB Graphic Adapter		X	NL571AA
HP DisplayPort Cable Kit	X	X	VN567AA
HP DisplayPort To Dual Link DVI-D Adapter	X	X	NR078AA
HP DisplayPort To DVI-D Adapter	X	X	FH973AA
HP DisplayPort to HDMI Adapter	X	X	BP937AA
HP DisplayPort to VGA Adapter	X	X	AS615AA
HP DMS-59 to Dual DVI Cable		X	DL139A
HP DMS-59 to Dual DisplayPort Adapter		X	XP688AA

### Data Storage Drives and Accessories

	DM	SFF/TWR	Part Number
HP 500-GB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive		X	QK554AA
HP 1-TB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive		X	QK555AA
HP 128-GB SATA 3.0Gb/s Solid State Drive	X	X	QV063AA
HP 160-GB SATA 3.0Gb/s Solid State Drive	X	X	QV064AA*
HP 500-GB SATA 3.0Gb/s Solid State Hybrid Drive	X	X	E1C62AA
HP Slim Removable SATA Hard Drive Enclosure (frame & carrier)		X	C1N41AA
HP Slim Removable SATA Hard Drive Enclosure (carrier only)		X	E3F39AA
HP Chassis (1bay) Security Kit		TWR only	AR639AA

\*Not available in all regions.

### Input Devices

	DM	SFF/TWR	Part Number
HP USB Keyboard	X	X	QY776AA
HP USB Gray Keyboard	X	X	B6B64AA
HP USB Smart Card (CCID) Keyboard	X	X	BV813AA
HP USB Keyboard and Mouse Kit	X	X	B1T09AA
HP USB Washable Keyboard	X	X	VF097AA
HP USB and PS/2 Washable Mouse	X	X	BM866AA
HP USB and PS/2 Washable Keyboard and Mouse Kit	X	X	BU207AA
HP PS/2 Mouse	X	X	QY775AA
HP USB Mouse	X	X	QY777AA
HP USB 1000dpi Laser Mouse	X	X	QY778AA
HP Wireless Keyboard and Mouse Combination*	X	X	QY449AA

\*Keyboard contains 25% post-consumer recycled plastic material

After-Market Options (availability may vary by region)

<b>System Memory</b>	<b>DM</b>	<b>SFF/TWR</b>	<b>Part Number</b>
HP 4GB DDR3-1600 (PC3-12800) DIMM		X	B4U36AA
HP 8GB DDR3-1600 (PC3-12800) DIMM		X	B4U37AA
HP 4GB DDR3-1600 (PC3-12800) SODIMM	X		B4U39AA
HP 8GB DDR3-1600 (PC3-12800) SODIMM	X		B4U40AA

<b>Multimedia Devices</b>	<b>DM</b>	<b>SFF/TWR</b>	<b>Part Number</b>
HP Slim DVD-ROM Drive		X	VP033AA
HP Slim SuperMulti DVD Writer Drive		X	QS209AA
HP USB HD 720P v2 Business Webcam	X	X	D8Z08AA
HP Business Headset	X	X	QK550AA
HP USB Business Speakers	X	X	D9J19AA

<b>Removable Media Storage</b>	<b>DM</b>	<b>SFF/TWR</b>	<b>Part Number</b>
HP 15-n-1 Media Card Reader (available March 2014)		X	TBD

<b>Security Devices</b>	<b>DM</b>	<b>SFF/TWR</b>	<b>Part Number</b>
HP Solenoid Lock and Hood Sensor (SFF)		SFF only	E0X97AA
HP Solenoid Lock and Hood Sensor (TWR)		TWR only	E0X96AA
HP SFF Wall Mount/Security Sleeve		SFF only	VN570AA
HP UltraSlim Cable Lock	X	X	H4D73AA

<b>Stands and Accessories</b>	<b>DM</b>	<b>SFF/TWR</b>	<b>Part Number</b>
HP Ai2 Convenience Stand (DM)	X		<i>Pending</i>
HP Integrated Work Center Stand (SFF)		SFF only	QP897AA
HP SFF Tower Stand		SFF only	VN569AA
HP DM Tower Stand	X		<i>Pending</i>
HP 600/800 Tower Bezel Kit		TWR only	E1C66AA
HP 800/600 SFF Bezel Kit		SFF only	E3F27AA
HP Serial Port Adapter (RS-232 compatible)		X	PA716A
HP Parallel Port Kit		X	KD061AA
Belkin USB to Serial Adapter	X		EM449AA

<b>LANDesk Software (E-Delivery)</b>	<b>Part Number</b>
LANDesk Management Suite License - 1-499 Nodes E-Delivery	QY369AAE
LANDesk Management Suite License - 500-999 Nodes E-Delivery	QY370AAE
LANDesk Management Suite License - 1000-1999 Nodes E-Delivery	QY371AAE
LANDesk Management Suite License - 2000-4999 Nodes E-Delivery	QY372AAE
LANDesk Management Suite License - 5000-9999 Nodes E-Delivery	QY373AAE
LANDesk Security Suite License E-Delivery	QY379AAE
LANDesk Management Suite 1 Year Maintenance - 1-499 Nodes E-Delivery	HZ825AAE



### After-Market Options (availability may vary by region)

LANDesk Management Suite 1 Year Maintenance - 500-999 Nodes E-Delivery	HZ826AAE
LANDesk Management Suite 1 Year Maintenance - 1000-1999 Nodes E-Delivery	HZ827AAE
LANDesk Management Suite 1 Year Maintenance - 2000-4999 Nodes E-Delivery	HZ828AAE
LANDesk Management Suite 1 Year Maintenance - 5000-9999 Nodes E-Delivery	HZ829AAE
LANDesk Security Suite 1 Year Subscription	HZ830AAE
LANDesk Patch Management 1 Year Subscription - 1-499 Nodes E-Delivery	HZ831AAE
LANDesk Patch Management 1 Year Subscription - 500-999 Nodes E-Delivery	HZ832AAE
LANDesk Patch Management 1 Year Subscription - 1000-1999 Nodes E-Delivery	HZ833AAE
LANDesk Patch Management 1 Year Subscription - 2000-4999 Nodes E-Delivery	HZ834AAE
LANDeskPatch Management 1 Year Subscription - 5000-9999 Nodes E-Delivery	HZ835AAE
LANDeskPatch Management 1 Year Subscription - 5000-9999 Nodes E-Delivery	HZ835AAE

© Copyright 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft, Windows and Windows 7 are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel and Core are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.